



General purpose ribbon designed for fabric labels

Key benefits

- Designed for intensive printing
- Resistant to textile cleaning processes
- Certified OEKO-TEX® Standard 100 for maximum confidence on all textile applications

Applications

- Garment labels
- Outdoor equipment labels
- Automotive interior labels



Recommended substrates

Nylon taffeta	● ● ● ● ●
Satin polyester	● ● ● ● ●
Polyester taffeta	● ● ● ● ●

Print quality

Barcode	● ● ● ● ●
Darkness	● ● ● ● ●
Small characters	● ● ● ● ●

Print resistance

Washing	● ● ● ● ●
Dry cleaning	● ● ● ● ●
Ironing	● ● ● ● ●

Printer parameters

Maximum speed: 8 ips (200 mm/s)

Heat settings:



Technical specifications

Film thickness: 4,5µm
 Total ribbon thickness: <8µm
 Ink melting point: 75°C | 167°F
 Coefficient of friction: Kd < 0,2
 Ink blackness: 1,8 ODR
 Antistatic designed

Approvals

OEKO-TEX® Standard 100 - Class I
 - CQ1172/1 IFTH
 REACH / SVHC 1907/2006/EC
 EU Food Contact 1935/2004/EC
 RoHS / Heavy Metals 2011/65/EU
 California Proposition 65
 Halogens IEC 61249-2-21:2003

Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature

Colours

- ATX 7
- ATX 7R (Pantone 185 C)
- ATX 7B (Pantone Process Blue C)
- ATX 7W (White)
- ATX 7UW (Ultra White)