



## ALPHA-3R – Portable Direct Thermal Printer

# SIMPLIFY YOUR EVERYDAY MOBILE PRINTING NEEDS



### KEY FEATURES

- TSC Designed & Manufactured
- IP54-rated protective case to resist dust and water
- Plastic design with rubber over-mold construction that withstands 1.5 m (5 ft) drop
- Wired & wireless communication interfaces: USB 2.0, RS-232, Bluetooth, and 802.11 b/g/n
- High capacity 2500 mAh rechargeable Li-ion batteries
- Large paper capacity to reduce the frequency of changing paper roll
- High-speed processor and extensive memory for fast print speeds of up to 102 mm (4") per second
- Lasts more than 12 hours of printing receipts on a single battery charge
- Supports TSPL-EZ (EPL and ZPL emulations) or CPCL emulation
- 2-Year Warranty is longer than other competitor's warranty

### APPLICATIONS

- Direct Store Deliveries (DSD)
- Field Repair/Installation
- Mobile Point-of-Sale
- Parking Citations
- Mobile Ticketing
- Onboard Transportation Ticketing
- Utility Billing/Meter Reading

## ALPHA-3R – Portable Direct Thermal Printer

PRINTER MODEL	Alpha-3R
Resolution	8 dots/mm (203 DPI)
Printing method	Direct Thermal
Max. print speed	102 mm (4")/second
Max. print width	72 mm (2.83")
Max. print length	2,286 mm (90")
Enclosure	Plastic with rubber over-mold construction
Physical dimension	116 mm (W) x 148 mm (H) x 70 mm (D) 4.57"(W) x 5.83"(H) x 2.75"(D)
Weight (including battery)	0.55 kg (1.212 lbs)
Drop specification	1.5 m (5 ft)
IP rating	IP54 (w/case)
Max. roll capacity	Receipt: 57 mm (2.25") OD Label: 55 mm (2.16") OD
Processor	32-bit RISC CPU
Memory	<ul style="list-style-type: none"> <li>• 4 MB Flash memory</li> <li>• 8 MB SDRAM</li> </ul>
Interface	<ul style="list-style-type: none"> <li>• USB 2.0</li> <li>• 802.11 b/g/n Wireless (factory option)</li> <li>• Bluetooth (factory option)</li> <li>• RS-232 (user option)</li> </ul>
Power	Two-cell, 7.4V DC, 2500 mAh Li-ion rechargeable battery
Operation switch, button	<ul style="list-style-type: none"> <li>• 3 buttons (On/off, feed, and cover-open)</li> <li>• 2 color LED for printer status, 3 LEDs for battery status</li> </ul>
Sensors	<ul style="list-style-type: none"> <li>• Reflective sensor</li> <li>• Head open sensor</li> </ul>
Internal fonts	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• One Monotype Imaging® CG Triumvirate Bold Condensed scalable font</li> </ul>
Bar code	<ul style="list-style-type: none"> <li>• 1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar</li> <li>• 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec</li> </ul>
Printer language	TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II) or CPCL emulation
Media type	Receipt paper, Bline receipt paper (Black mark in printing side) & Selected label
Media width	Receipt: 50.8 ~ 80 mm (2" ~ 3.15") Label: 50.8 ~ 78 mm (2" ~ 3.07")
Media thickness	Receipt: 0.0508 ~ 0.1016 mm (2 ~ 4 mil) Label: Fasson standard label media up to 0.14 mm (5.5 mil)
Media height	Label: Min. 25.4 mm (1")
Media core diameter	10.2 ~ 25.4 mm (0.4" ~ 1")
Environment condition	Operation: -10 ~ 50 °C (14 ~ 122 °F), 10 ~ 90% non-condensing Storage: -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 90% non-condensing
Safety regulation	FCC, CE, CB, CCC, C-Tick
Environmental concern	Comply with RoHS, WEEE
Accessories	<ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• Quick start guide</li> <li>• Belt Clip</li> <li>• Li-ion battery</li> <li>• Power adapter</li> </ul>
Limited warranty	<ul style="list-style-type: none"> <li>• Printer: 2 years</li> <li>• Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>• Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>
Factory options	<ul style="list-style-type: none"> <li>• 802.11 b/g/n Wireless network</li> <li>• Bluetooth module</li> </ul>
User options	<ul style="list-style-type: none"> <li>• USB to RS-232 converter cable</li> <li>• USB cable</li> <li>• Li-ion battery</li> <li>• Charge station 1 cell (with changeable power connector)</li> <li>• Vehicle power adapter</li> <li>• IP54-rated protective case with shoulder strap</li> </ul>



### CORPORATE HEADQUARTERS

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 2 2218 6789  
E-mail: printer\_sales@tscprinters.com

### LI ZE PLANT

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 3 990 6677  
E-mail: printer\_sales@tscprinters.com

### AMERICAS

**TSC Auto ID Technology America Inc. Corporate Office**  
Tel: +1 909 525 9779  
E-mail: sales@tscprinters.com

**Orlando Office**  
Tel: +1 407 704 8918  
E-mail: sales@tscprinters.com

### CANADA

**TSC Auto ID Technology America Inc.**  
Tel: +1 909 525 9779  
E-mail: sales@tscprinters.com

### MEXICO

**TSC Mexico Representative Office**  
Tel: +52 (33) 3836 6682  
E-mail: sales@idc-componentes.com

### BRAZIL

**TSC Brazil Representative Office**  
Tel: +55 (11) 9597 8098  
E-mail: sales@tscprinters.com

### EMEA

**TSC Auto ID Technology EMEA GmbH**  
Tel: +49 (0) 8106 37979 00  
E-mail: info@tsc.eu.com

### RUSSIA

**TSC Auto ID Technology EMEA GmbH**  
Tel: +7 915 422 8889  
E-mail: info@tsc.eu.com

### MIDDLE EAST

**TSC Auto ID Technology ME Ltd, FZE**  
Tel: +971 4 2533 069  
E-mail: info@tscmea.com

### ASIA PACIFIC

**TSC Auto ID Technology Co., Ltd.**  
Tel: +886 2 2218 6789  
E-mail: printer\_sales@tscprinters.com

### CHINA

**Tianjin TSC Auto ID Technology Co., Ltd.**  
Tel: +86 22 5981 6661  
E-mail: sale@tscprinters.com.cn

TSC® is a trademark of TSC Auto ID Technology Co., Ltd. TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company. © 2013 TSC Auto ID Technology Co., Ltd. Product models and Specifications are subject to change without notice. Contact your TSC sales representative for specific information.